## WEST Generate Collection Print

L10: Entry 1 of 3

File: PGPB

Apr 25, 2002

PGPUB-DOCUMENT NUMBER: 20020049137

PGPUB-FILING-TYPE: new

DOCUMENT-IDENTIFIER: US 20020049137 A1

TITLE: Composite oxide, process for producing the same, catalyst for purifying

exhaust gas, and process for producing the same

PUBLICATION-DATE: April 25, 2002

INVENTOR-INFORMATION:

| NAME             | CITY  | STATE | COUNTRY | RULE-47 |
|------------------|-------|-------|---------|---------|
| Morikawa, Akira  | Aichi |       | JP      |         |
| Hatanaka, Miho   | Aichi | ,     | JP      |         |
| Imagawa, Haruo   | Aichi |       | JP .    |         |
| Suda, Akihiko    | Aichi |       | ĴΡ      |         |
| Takahashi, Naoki | Aichi |       | JP      |         |

ASSIGNEE-INFORMATION:

NAME CITY STATE COUNTRY TYPE CODE KABUSHIKI KAISHA TOYOTA CHUO KENKYUSHO Aichi-qun JP 03

APPL-NO: 09/ 911489 [PALM] DATE FILED: July 25, 2001

FOREIGN-APPL-PRIORITY-DATA:

| COUNTRY | APPL-NO     | DOC-ID             | APPL-DATE         |
|---------|-------------|--------------------|-------------------|
| JP      | 2000-227183 | 2000JP-2000-227183 | July 27, 2000     |
| JP      | 2000-379295 | 2000JP-2000-379295 | December 13, 2000 |
| JP      | 2000-394738 | 2000JP-2000-394738 | December 26, 2000 |
| JP      | 2001-61422  | 2001JP-2001-61422  | March 6, 2001     |
| JP      | 2001-164444 | 2001JP-2001-164444 | May 31, 2001      |

INT-CL: [07] <u>B01</u> <u>J</u> <u>23/10</u>

US-CL-PUBLISHED: 502/351; 502/304, 502/341, 502/251, 502/242 US-CL-CURRENT: 502/351; 502/242, 502/251, 502/304, 502/341

REPRESENTATIVE-FIGURES: NONE

## ABSTRACT:

A composite oxide includes agglomerated particles which have an average particle diameter of 20 .mu.m or less, which are composed of a plurality of metallic element oxides being in form of fine particles having an average diameter of 50 nm or less, and which have a surface and an inner portion whose metallic element distributions differ with each other. The characteristics of the respective metallic elements are exhibited maximally. Hence, it is extremely useful as a support for an exhaust gas purifying catalyst. The catalyst exhibits the activities which degrade less even after it is subjected to a sever durability, is good in terms of the heat and sulfur-poisoning resistance, and can efficiently purify the harmful components in

exhaust gases. Moreover, it is possible to produce such a composite oxide and catalyst easily and stably by production processes disclosed herein.